

#### **PERFORMANCE COATINGS**

### Lanco™ Flow P 30

Flow Booster for Powder Coatings

Lanco™ Flow is a flow boosting additive for powder coatings. A co-additive to be used in conjunction with acrylic flow promoters to increase their efficiency. Lanco Flow P 30 improves the surface appearance of powder coatings. It is also effective processing aid to improve extrusion throughput and aids pigment dispersion in powder coatings during the manufacturing process. Additionally, Lanco Flow P30 will improve degassing and flow & levelling properties while having a minimal impact on coating gloss.

### **FEATURES AND BENEFITS**

- · Contains Bio-Based Content
- Degassing

- Flow & Leveling
- Minimal Gloss Impact

### **CHARACTERISTICS**

Characteristic Name	Value
Addition Levels (% on total formula)	The recommended addition level of Lanco Flow P 30 is 1-2%, based on total resin used. The optimum level of addition depends on the coating formulation. Please note: An acrylic flow modifier is still necessary to achieve a defect free surface.
Appearance	White powder
Chemical Type	Oleo-based modified wax
Incorporation Recommendations	Lanco Flow P 30 should be incorporated into the premix prior to the extrusion step.
Melting Point (°C)	87
Particle Size Dv50 (µm)	≤ 20
Storage & Handling	Store bags on pallets in closed areas. A storage temperature of 30°C should not be exceeded.

# **APPLICATIONS**

• Industrial OEM Coatings

Published on 25 Jan, 2024 Page 1 of 3

 $Lanco^{TM}$  Flow P 30 Performance Coatings

### **AVAILABLE REGIONS**

- Asia Pacific
- EMEAI
- Latin America
- North America

#### **RECOMMENDED STORAGE AND RE-TEST DATE**

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

#### **REGULATORY STATUS**

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAlCustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

# **DISCLAIMER**

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

Published on 25 Jan, 2024 Page 2 of 3

Lanco TM Flow P 30 Performance Coatings

# COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 25 Jan, 2024 Page 3 of 3