



AUTOMOTIVE COATINGS PRODUCT GUIDE

RESINS, DISPERSANTS & WAX ADDITIVES

Lubrizol

Performance Coatings

www.lubrizol.com/coatings



COMPREHENSIVE SOLUTIONS PROVIDER FOR AUTOMOTIVE COATINGS

Lubrizol provides innovative solutions for Automotive OEM and Vehicle Refinish, including interior and underbody. We deliver decades of application expertise to enhance the performance and durability of automotive coatings. Our approach is to understand what is important to coating manufacturers, automotive manufacturers and consumers so that Lubrizol can address the challenges important to the industry. We help our customers meet rigorous OEM specifications, resulting in value-added, long-lasting coatings.



Comprehensive Product Portfolio

We offer OEM and refinish coating manufacturers a diverse portfolio of resins and polymers, dispersants and additives that contribute to the appearance, protection, adhesion and resilience of automotive exterior and interior coatings. Whether you need a solvent-based or water-based system, Lubrizol can help meet your benchmarks for performance, efficiency and profitability.

To find the ideal solution, our technical service specialists work side-by-side with customers to personally guide them through the product selection process. To address unique challenges, we can tailor a formulation to meet customer-specified production and performance requirements.

LUBRIZOL TECHNOLOGIES

Automotive OEM and Vehicle Refinish Expertise

Lubrizol's technology helps exterior automotive coatings shine in the demanding environments to which they are exposed. Our solutions provide customers enhanced coating durability, protecting the finish from corrosion, chemicals, scratches and UV damage. We deliver aesthetic qualities that enhance color and vibrancy, provide high initial and long-term gloss and exceptional overall appearance. Our leading dispersion technology enables formulators the ability to disperse and stabilize high performance colors and effect pigments.

Interior Protection

Lubrizol's products are an innovative choice for factory-applied, water-based and solvent-based plastic coatings. We provide solutions to protect a wide range of plastic substrates such as instrument panels, gauge clusters and door panels, including end applications made of hard plastics such as ABS, PC-ABS, PC and HIPS. Lubrizol offers dependable protection, meeting automotive OEM performance specifications for surface cleaners and protectants, sunscreen, lotions and insect repellants. Additionally, we bring protection from water, alkaline and acidic solutions, scratch, abrasion and print resistance.



Global Support and Service

In manufacturing, innovation is nothing without reliability. That's why our automotive products are backed by a worldwide system of analytical, service and technical support. From application consultation to individualized formulation to the confidence that comes with supply security, Lubrizol is always ready to help.

Dispersants for Automotive OEM Applications						
Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Organic	Inorganic	Carbon Black
Solsperse™ 5000s	Synergist	•		•		•
Solsperse™ 12000s	Synergist	•	•	•		•
Solsperse™ 22000	Synergist	•		•		
Solsperse™ 20000	Polymeric Dispersant	•	•	•		•
Solsperse™ 27000	Polymeric Dispersant		•	•		•
Solsperse™ 32500	Polymeric Dispersant	•		•		•
Solsperse™ 32600	Polymeric Dispersant	•		•		•
Solsperse™ 35100	Polymeric Dispersant	•		•		
Solsperse™ 36600	Polymeric Dispersant	•			•	
Solsperse™ 37500	Polymeric Dispersant	•		•		•
Solsperse™ 46000	Polymeric Dispersant		•	•	•	•
Solsperse™ 75500	Polymeric Dispersant	•		•		•
Solsperse™ 76500	Polymeric Dispersant	•		•	•	•
Solsperse™ 83500	Polymeric Dispersant	•		•		
Solsperse™ 84500	Polymeric Dispersant	•			•	
Solsperse™ 85000	Polymeric Dispersant	•			•	
Solsperse™ M387	Polymeric Dispersant	•		•	•	•
Solsperse™ W100	Polymeric Dispersant		•	•	•	•
Solsperse™ W210	Polymeric Dispersant		•	•		•
Solsperse™ W320	Polymeric Dispersant	•			•	
Solsperse™ WV 400	Polymeric Dispersant		•	•	•	•

Dispersants for Automotive OEM Applications (Continued)				
Lubrizol Product	Key Benefits and Features	Physical Description	% Active Ingredient	Solvent
Solsperse™ 5000s	Enhanced performance when used with a hyperdispersant in solvent-based systems; for use with difficult-to-disperse blue/green, carbon black pigments.	Blue Powder	100	–
Solsperse™ 12000s	Enhanced performance when used with a hyperdispersant in a water- or alcohol-based system; compatible with difficult-to-disperse organic blue/green and carbon black pigments.	Blue Powder	100	–
Solsperse™ 22000	Enhanced performance when used with a hyperdispersant in a solvent-based system; compatible with difficult-to-disperse red, orange and yellow organic pigments.	Yellow Powder	100	–
Solsperse™ 20000	Increased pigment wetting and tintorial properties; improved performance of poor wetting resins; produces highly pigmented concentrates making it ideal for mixing schemes.	Amber Liquid	100	–
Solsperse™ 27000	For use in resin-containing systems; compatible with organic and carbon black pigments.	Pale Yellow-Amber Viscous Liquid	100	–
Solsperse™ 32500	For use with carbon black and organic pigments; high pigment loading.	Pale Yellow-Brown Liquid	40	Butyl Acetate
Solsperse™ 32600	For use with carbon black and organic pigments; high pigment loading.	Pale Yellow-Brown Liquid	40	Aromatic 100
Solsperse™ 35100	For use with high performance, organic and effect pigments; high pigment loading.	Pale Yellow-Brown Liquid	40	Butyl Acetate
Solsperse™ 36600	For use with TiO ₂ and other inorganic pigments; high tint strength and opacity.	Colorless-Yellow Viscous Liquid	50	Aromatic 100
Solsperse™ 37500	For use with high surface area carbon blacks; improved jetness; high pigment loading.	Dark Brown Liquid	40	Butyl Acetate
Solsperse™ 46000	For use in resin-free grind systems for organic and inorganic pigments.	Pale Yellow Viscous Liquid	50	Water
Solsperse™ 75500	Improved pigment dispersion & stability.	Yellow to Amber Liquid	40	Butyl Acetate
Solsperse™ 76500	For use with organic, inorganic, and aluminum pigments; very high pigment loadings; compatible with CAB.	Pale Yellow Viscous Liquid	50	Butyl Acetate
Solsperse™ 83500	High performance dispersant effective across a wide range of pigments and systems; particularly effective on organic reds and yellows.	Colorless to Yellow Liquid	40	PMA/Butyl Acetate (40/10)
Solsperse™ 84500	Increased pigment concentration with improved rheological characteristics and stability of dispersion.	Colorless to Yellow Viscous Liquid	50	MPA
Solsperse™ 85000	Dispersion of TiO ₂ with high filler loadings and improved wetting/dispersion.	Colorless to Yellow Viscous Liquid	100	–
Solsperse™ M387	High performance for formulation of multi-media solvent-based dispersions; increased millbase pigment loadings; excellent compatibility in a wide range of resins and solvents; can be used to produce zero VOC ¹ colorants.	Yellow to Brown Viscous Liquid	100	–
Solsperse™ W100	Highly pigmented resin-free and resin-minimal dispersions, on a wide range of particles including organics, inorganics and carbon black.	Yellow to Amber Liquid	40	Water
Solsperse™ W210	Rapid pigment wetting and improved dispersion stability while enabling optimal tinting strength & color development; biocide-free.	Amber Liquid	100	–
Solsperse™ W320	Improved dispersion & stability of transparent iron oxides and inorganics.	Pale Yellow to Amber Liquid	40	Water
Solsperse™ WV 400	High performance dispersant that maximizes the pigment loading in the grind stage to improve production efficiency; for use in resin-free and resin-minimal formulations; high degree of viscosity and particle size stability.	Yellow-Brown Liquid	40	–

¹Can be used for coating formulations where ultra low to zero VOC content is desired.

Resins for Automotive OEM Applications

Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Role in Coating System	Key Benefits and Features
Carbaset® CR-7181	Self-Crosslinking Acrylic Polymer		•	Resin for topcoat and/or primer for plastic substrates	Offers high gloss; excellent adhesion to variety of plastic substrates (ABS, Lexan, Noryl); excellent UV resistance.
Carbaset® CR-7185	Acrylic Polymer		•	Resin for topcoat and/or primer for plastic substrates	Offers high gloss; excellent adhesion to variety of plastic substrates (ABS, Lexan, Noryl); excellent UV, gasoline, and solvent resistance; low VOC ¹ . Blendable polymer with polyurethanes.
Carbaset® CA-7160 RC	Styrene-Acrylic		•	Resin for sound dampening membranes	Offers excellent balance of binding and mechanical properties in high filled systems.
Carbaset® PC-27	Self-Crosslinking Acrylic Polymer		•	Resin for topcoat and/or primer for rigid plastic substrates	Offers superior resistance to sunscreens, insect repellents, surface cleaners and protectants; excellent scratch, abrasion and print resistance; passes GMW-14445; excellent adhesion to a variety of rigid plastic substrates (ABS, Lexan, Noryl).
Carbaset® PL-958 Carbaset® PL-958B*	Acrylic Polymer		•	Resin for factory/field applied peelable temporary coatings	Offers easy peelability with no residue; high tensile strength and very good solvent resistance; can be formulated into a clear or pigmented temporary/protective coating.
Permax™ 805	Vinylidene Chloride Copolymer		•	Resin for underbody/undercarriage coatings requiring corrosion resistance; maintenance primers; rust converting primers	Excellent protection from corrosion/rust; improved adhesion to a wide range of metal surfaces; superior shelf stability to competitive products; APEO free ² .
Sancure™ PC-55	Aliphatic Polyurethane Dispersion		•	Polyurethane system for 2k plastic coatings	Offers superior resistance to sunscreens, insect repellents, surface cleaners and protectants; excellent balance of mar resistance with soft tactile feel; excellent UV resistance and NMP-free ³ ; low VOC ¹ .

*Carbaset® PL-958B is equivalent to Carbaset® PL-958. Carbaset PL-958 is produced in North America using domestically-sourced raw materials. Carbaset PL-958B is produced in Europe using domestically-sourced raw materials.

Performance Additives for Automotive OEM Applications

Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Role in Coating System
Lanco™ 1380 F	Surface Modifier	•	•	Surface protection
Lanco™ Flow L		•		Flow and leveling agents
Lanco™ Flow U		•		Flow and leveling agents
Lanco™ Glidd 9530 C	Surface Modifier		•	Surface protection
Lanco™ TF 1780 C/ TF 1780 EFC	Surface Modifier	•	•	Surface protection
Lanco™ TFW 1765 NC	Surface Modifier		•	Surface protection
Lanco™ Matt 2000	Surface Modifier	•	•	Matting agent
Lubrizol® 2063	Surface Modifier	•	•	Promotes adhesion to metal substrates
Solthix™ 250	Rheology Modifier	•		Viscosity and flow control
Solthix™ A100	Rheology Modifier		•	Viscosity and flow control
Solthix™ A200	Rheology Modifier		•	Viscosity and flow control

Resins for Automotive OEM Applications (Continued)

Lubrizol Product	Physical Description	Weight Solids (%)	Specific Gravity	MFFT (°C)	pH
Carbaset® CR-7181	Milky-White Emulsion	41.5	1.06	90	8.5-9.5
Carbaset® CR-7185	Milky-White Emulsion	42.5	1.03	44	8.0
Carbaset® CA-7160 RC	Milky-White Emulsion	49.0	1.01	21	8.3
Carbaset® PC-27	Milky-White Emulsion	42.0	1.05	90	8.0-9.0
Carbaset® PL-958 Carbaset® PL-958B*	Milky-White Emulsion	41.5	1.07	<3	8.0
Permax™ 805	Milky-White Emulsion	41.5	1.28	13.5	1.0-2.2
Sancure™ PC-55	Translucent Dispersion	42.0	1.05	—	8.0

¹Can be used for coating formulations where less than 75 g/l VOC is desired (as measured by EPA Method 24).

²APEO not intentionally added to the composition or used in manufacture.

³NMP not intentionally added to the composition or used in manufacture.

Performance Additives for Automotive OEM Applications (Continued)

Lubrizol Product	Key Benefits and Features	Physical Description	Solids (%)	Solvent
Lanco™ 1380 F	Improves scratch resistance, provides matting effect with excellent anti-burnishing, smooth surface feel.	White Powder	100	
Lanco™ Flow L	Improves appearance of film by eliminating pin holes, craters and fisheyes, reduces orange peel appearance, post-addable and recoatable.	Clear Colorless Liquid	95	Xylene
Lanco™ Flow U	Improves appearance of film by eliminating pin holes, craters and fisheyes, reduces orange peel appearance, post-addable and recoatable.	Colorless to Pale Yellow Liquid	100	
Lanco™ Glidd 9530 C	Improves scratch and abrasion resistance, easily incorporated by simple stirring.	Milky-White Dispersion	30	Water
Lanco™ TF 1780 C/ TF 1780 EFC	Excellent improvement in scratch and abrasion resistance, excellent water repelling properties, used in solvent-based and powder coatings.	White Powder	100	
Lanco™ TFW 1765 NC	Offers excellent scratch and abrasion resistance, excellent surface smoothness, excellent surface smoothness, very good metal marking resistance, used in water-based coatings.	White Powder	100	
Lanco™ Matt 2000	Combines uniform matting control with excellent dispersibility. Provides good scratch and mar resistance properties.	White Powder	100	
Lubrizol® 2063	DTM adhesion promoter with broad resin compatibility for ferrous metal and aluminum especially in water-based systems; metallic pigment passivation.	Clear Liquid	56	Butyl Cellosolve
Solthix™ 250	Excellent sag resistance and pigment suspension; minimal impact on gloss; high flop index potential.	Pale Yellow Liquid	40	PM Acetate
Solthix™ A100	Highest thixotropic index; high efficiency; excellent sag resistance and pigment suspension; minimal impact on gloss; high flop index potential.	Milky-White Emulsion	30	Water
Solthix™ A200	High thixotropic index; excellent sag resistance and pigment suspension; minimal impact on gloss; high flop index potential.	Milky-White Emulsion	30	Water

Dispersants for Vehicle Refinish (VR) Applications						
Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Organic	Inorganic	Carbon Black
Solsperse™ 5000s	Synergist	•		•		•
Solsperse™ 12000s	Synergist	•	•	•		•
Solsperse™ 22000	Synergist	•		•		
Solsperse™ 20000	Polymeric Dispersant	•	•	•		•
Solsperse™ 27000	Polymeric Dispersant		•	•		•
Solsperse™ 32600	Polymeric Dispersant	•		•		•
Solsperse™ 35100	Polymeric Dispersant	•		•		•
Solsperse™ 36600	Polymeric Dispersant	•			•	
Solsperse™ 37500	Polymeric Dispersant	•		•		
Solsperse™ 46000	Polymeric Dispersant		•	•	•	•
Solsperse™ 75500	Polymeric Dispersant	•		•		•
Solsperse™ 76500	Polymeric Dispersant	•		•	•	•
Solsperse™ 83500	Polymeric Dispersant	•		•		•
Solsperse™ 84500	Polymeric Dispersant	•			•	
Solsperse™ 85000	Polymeric Dispersant	•				
Solsperse™ M387	Polymeric Dispersant	•		•	•	•
Solsperse™ W100	Polymeric Dispersant		•	•	•	•
Solsperse™ W210	Polymeric Dispersant		•	•		•
Solsperse™ W320	Polymeric Dispersant	•			•	
Solsperse™ WV 400	Polymeric Dispersant		•	•	•	•

Dispersants for Vehicle Refinish (VR) Applications (Continued)				
Lubrizol Product	Key Benefits and Features	Physical Description	% Active Ingredient	Solvent
Solsperse™ 5000s	Enhanced performance when used with a hyperdispersant in solvent-based systems; for use with difficult to disperse blue/green, carbon black pigments.	Blue Powder	100	–
Solsperse™ 12000s	Enhanced performance when used with a hyperdispersant in a water or alcohol-based system; compatible with difficult-to-disperse organic blue/green and carbon black pigments.	Blue Powder	100	–
Solsperse™ 22000	Enhanced performance when used with a hyperdispersant in a solvent-based system; compatible with difficult-to-disperse red and yellow organic pigments.	Yellow Powder	100	–
Solsperse™ 20000	Increased pigment wetting and tintorial properties; improved performance of poor wetting resins; produces highly pigmented concentrates making it ideal for mixing schemes.	Amber Liquid	100	–
Solsperse™ 27000	For use in very low resin-containing systems; compatible with organic and carbon black pigments.	Pale Yellow-Amber Viscous Liquid	100	–
Solsperse™ 32600	For use with carbon black and organic pigments; high pigment loading.	Orange/Yellow Viscous Liquid	40	Aromatic 100
Solsperse™ 35100	For use with high performance, organic and effect pigments; high pigment loading.	Pale Yellow-Brown Liquid	40	Butyl Acetate
Solsperse™ 36600	For use with TiO ₂ and other inorganic pigments; high tint strength and opacity.	Colorless-Yellow Viscous Liquid	50	Aromatic 100
Solsperse™ 37500	For use with high surface area carbon blacks; improved jetness; high pigment loading.	Dark Amber/Brown Liquid	40	Butyl Acetate
Solsperse™ 46000	For use in resin-free grind systems for organic and inorganic pigments.	Yellow Viscous Liquid	50	Water
Solsperse™ 75500	Improved pigment dispersion & stability.	Yellow to Amber Liquid	40	Butyl Acetate
Solsperse™ 76500	For use with organic, inorganic and aluminum pigments; very high pigment loadings; compatible with CAB.	Yellow/Brown Liquid	50	Butyl Acetate
Solsperse™ 83500	High performance dispersant effective across a wide range of pigment and systems; particularly effective on organic reds and yellow.	Colorless to Yellow Liquid	40	PMA/Butyl Acetate (40/10)
Solsperse™ 84500	Increased pigment concentration with improved rheological characteristics and stability of dispersion.	Colorless to Yellow Viscous Liquid	50	MPA
Solsperse™ 85000	Dispersion of TiO ₂ with high filler loadings and improved wetting/dispersion.	Colorless to Yellow Viscous Liquid	100	–
Solsperse™ M387	For high performance formulation of multi-media solvent-based dispersions; increased millbase pigment loadings; excellent compatibility in a wide range of resins and solvents; can be used to produce zero VOC ¹ colorants.	Yellow to Brown Viscous Liquid	100	–
Solsperse™ W100	Highly pigmented resin-free and resin-minimal dispersions, on a wide range of particles including organics, inorganics and carbon black.	Yellow to Amber Liquid	40	Water
Solsperse™ W210	Rapid pigment wetting and improved dispersion stability while enabling optimal tinting strength and color development; biocide-free.	Amber Liquid	100	–
Solsperse™ W320	Improved dispersion and stability of transparent iron oxides and inorganics.	Pale Yellow to Amber Liquid	40	Water
Solsperse™ WV 400	High performance dispersant that maximizes the pigment loading in the grind stage to improve production efficiency; for use in resin-free and resin-minimal formulations; high degree of viscosity and particle size stability.	Yellow-Brown Liquid	40	–

¹Can be used for coating formulations where ultra low to zero VOC content is desired.

Resins for Vehicle Refinish (VR) Applications					
Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Role in Coating System	Key Benefits and Features
Carbaset® CR-7181	Self-Crosslinking Acrylic Polymer		•	Resin for top coat and/or primer for plastic substrates	Offers high gloss, excellent adhesion to variety of plastic substrates (ABS, Lexan, Noryl); excellent UV resistance.
Carbaset® CR-7185	Acrylic Polymer		•	Resin for top coat and/or primer for plastic substrates	Offers high gloss, excellent adhesion to variety of plastic substrates (ABS, Lexan, Noryl); excellent UV, gasoline, and solvent resistance; low VOC ¹ . Blendable polymer with polyurethanes.
Carbaset® CA-7160 RC	Styrene-Acrylic Polymer		•	Resin for sound dampening membranes	Offers excellent balance of binding and mechanical properties in high filled systems.
Carbaset® PC-27	Self-Crosslinking Acrylic Polymer		•	Resin for top coat and/or primer for rigid plastic substrates	Offers superior resistance to sunscreens, insect repellents, surface cleaners and protectants; excellent scratch, abrasion and print resistance; passes GMW-14445; excellent adhesion to a variety of rigid plastic substrates (ABS, Lexan, Noryl).
Carbaset® PL-958 Carbaset® PL-958B*	Acrylic Polymer		•	Resin for factory/field applied peelable temporary coatings	Offers easy peelability with no residue; high tensile strength and very good solvent resistance; can be formulated into a clear or pigmented temporary/protective coating.
Doresco® HS-4	Hydroxylated Solution Acrylic	•		Solution acrylic system for solvent-based primers	Quick hardening; excellent gloss and weather; yellowing resistance; high solid content; excellent adhesion on plastics and metal surfaces.
Doresco® OH38	Hydroxylated Solution Acrylic	•		Solution acrylic system for solvent-based primers and top coats	Quick hardening; excellent gloss and weather; yellowing resistance; high solid content; excellent adhesion on plastics and metal surfaces.
Doresco® OH60	Hydroxylated Solution Acrylic	•		Solution acrylic system for solvent-based primers and topcoats	Excellent gloss; excellent resistance to chemicals, light and weathering; excellent adhesion to metal surfaces.
Permax™ 805	Vinylidene Chloride Copolymer		•	Resin for underbody/undercarriage coatings requiring corrosion resistance; maintenance primers; rust converting primers.	Excellent protection from corrosion/rust; improved adhesion to a wide range of metal surfaces; superior shelf stability to competitive products. APEO free ² .
Sancure™ PC-55	Aliphatic Polyurethane Dispersion		•	Polyurethane system for 2k plastic coatings	Offers superior resistance to sunscreens, insect repellents, surface cleaners and protectants; excellent balance of mar resistance with soft tactile feel; excellent UV resistance and NMP-free ³ ; low VOC ¹ .

*Carbaset® PL-958B is equivalent to Carbaset® PL-958. Carbaset PL-958 is produced in North America using domestically-sourced raw materials. Carbaset PL-958B is produced in Europe using domestically-sourced raw materials.

Performance Additives for Vehicle Refinish (VR) Applications				
Lubrizol Product	Product Type	Suitable for Solvent-Based	Suitable for Water-Based	Role in Coating System
Lanco™ Flow L	Acrylic Flow Modifier	•		Flow and leveling agents
Lanco™ Flow U	Acrylic Flow Modifier	•		Flow and leveling agents
Solthix™ 250	Rheology Modifier	•		Viscosity and flow control
Solthix™ A100	Rheology Modifier		•	Viscosity and flow control
Solthix™ A200	Rheology Modifier		•	Viscosity and flow control

Resins for Vehicle Refinish (VR) Applications (Continued)								
Lubrizol Product	Physical Description	Weight Solids (%)	Specific Gravity	MFFT (°C)	pH	Acid Number	Hydroxyl Content (% Over Solids)	Solvent
Carbaset® CR-7181	Milky-White Emulsion	41.5	1.06	90	8.5-9.5	-	-	-
Carbaset® CR-7185	Milky-White Emulsion	42.5	1.03	44	8.0	-	-	-
Carbaset® CA-7160 RC	Milky-White Emulsion	49.0	1.01	21	8.3	-	-	-
Carbaset® PC-27	Milky-White Emulsion	42.0	1.05	90	8.0-9.0	-	-	-
Carbaset® PL-958 Carbaset® PL-958B*	Milky-White Emulsion	47.0	1.07	<3	8.0	-	-	-
Doresco® HS-4	Amber Liquid	69-72	-	-	-	7-10	4.3	Butyl Acetate
Doresco® OH38	Amber Liquid	42	-	-	-	<12	4%	(1:1)
Doresco® OH60	Amber Liquid	59-61	-	-	-	<10	3	Methoxy Propyl Acetate/ Xylene (1:1)
Permax™ 805	Milky-White Emulsion	60.0	1.28	13.5	1.0-2.2	-	-	-
Sancure™ PC-55	Translucent Dispersion	42.0	1.05	-	8.0	-	-	-

¹Can be used for coating formulations where less than 75 g/l VOC is desired (as measured by EPA Method 24).

²APEO not intentionally added to the composition or used in manufacture.

³NMP not intentionally added to the composition or used in manufacture.

Performance Additives for Vehicle Refinish (VR) Applications (Continued)				
Lubrizol Product	Key Benefits and Features	Physical Description	Solids (%)	Solvent
Lanco™ 1380 F	Improves scratch resistance, provides matting effect with excellent anti-burnishing, smooth surface feel.	White Powder	100	
Lanco™ Flow L	Improves appearance of film by eliminating pin holes, craters and fisheyes, reduces orange peel appearance, post-addable and recoatable.	Clear Colorless Liquid	95	Xylene
Lanco™ Flow U	Improves appearance of film by eliminating pin holes, craters and fisheyes, reduces orange peel appearance, post-addable and recoatable.	Colorless to Pale Yellow Liquid	100	
Lanco™ Glidd 9530 C	Improves scratch and abrasion resistance, easily incorporated by simple stirring.	Milky-White Dispersion	30	Water
Solthix™ A200	High thixotropic index; excellent sag resistance and pigment suspension; minimal impact on gloss; high flop index potential.	Milky-White Emulsion	30	Water

Lubrizol Locations

NORTH AMERICA

Lubrizol Advanced Materials, Inc.
9911 Brecksville Road
Brecksville, OH 44141 USA
+1.888.234.2436

EUROPE

Lubrizol Deutschland GmbH
Max-Planck-Str. 6
27721 Ritterhude Germany
+49.421.69333

ASIA-PACIFIC

Lubrizol Specialty Chemicals
(Shanghai) Co., Ltd
10/F, Park Center International
No. 1088 Fang Dian Road
Shanghai 201204, PR China
+8621.3866.0366

SOUTH AMERICA

Lubrizol do Brasil Aditivos Ltda
Avenida Nove de Julho, 3653
Jardim Paulista
Sao Paulo – SP
01407-000
+55.11.4097.0250

Lubrizol Performance Coatings is a market-driven innovator of specialty chemicals for advanced coatings, inks, and composites. Our portfolio of resin and additive technologies solve challenges across a wide range of markets and applications. Formulators choose Lubrizol to achieve unique performance, productivity, and sustainability benefits. More than just a supplier, we are a collaborator with extensive experience in surface protection, dispersion, adhesion, and barrier properties – working closely with customers to explore and develop truly differentiated solutions.



Performance Coatings

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.