

Doresco® AC4-74 Solution Acrylic

Tough and flexible solvent Borne thermoplastic acrylic resin

Doresco® AC4-74 is an adhesion promoted resin that is appropriate where toughness and flexibility are required on glass and metal substrates. Doresco AC4-74 is a thermoplastic solution acrylic resin specifically designed to provide adhesion to aluminum, glass, primed and unprimed steel and other metal substrates. Doresco AC4-74 is an adhesion promoted resin that exhibits improved adhesion to a wide variety of substrates. This resin possesses the right combination of toughness and flexibility which makes it appropriate for interior and exterior use. Doresco AC4-74 provides fast solvent release and generally produces films that resist blocking. Upon moderate aging, air dried applications will exhibit the same end properties as baked systems. Doresco AC4-74 is soluble in aromatics, ketones, esters and glycol ether esters. It tolerates alcohols and some aliphatics.

FEATURES AND BENEFITS

- Adhesion
- Toughness
- Flexible

CHARACTERISTICS

Characteristic Name	Value
% Weight Solids	45
Density (lb/gal @ 25 °C)	8
Tg (°C)	50

APPLICATIONS

- Industrial OEM Coatings
- Protective Coatings
- Transportation Coatings

AVAILABLE REGIONS

- Asia Pacific
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.