

#### PERFORMANCE COATINGS

#### PRODUCT DATA SHEET

# Carboset® 2309C Acrylic Emulsion

Carboset 2309C is an FDA and GB9685 compliant waterborne acrylic emulsion specifically developed for non-stick pan application. It is has good adhesion with filler particles and extremely low ash content. In addition, Carboset 2309C has good compatibility with typical fluoro-resins used in non-stick pan.

#### **FEATURES AND BENEFITS**

Adhesion

Non-Yellowing

## **CHARACTERISTICS**

Characteristic Name	Value
% Weight Solids	39.0 - 41.0
Brookfield Viscosity (cps)	0 - 75
pH Value	7.5 - 8.5

# **REGULATORY**

APEO-Free¹

• FDA

• GB9685

## **APPLICATIONS**

Analog Printing Coatings

#### **AVAILABLE REGIONS**

Asia Pacific

#### **RECOMMENDED STORAGE AND RE-TEST DATE**

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

## **REGULATORY STATUS**

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at

Published on 25 Apr, 2022 Page 1 of 2

Formaldehyde-Free¹

<sup>&</sup>lt;sup>1</sup>Not intentionally added to the composition of this product

Carboset® 2309C Performance Coatings

#### www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

#### **DISCLAIMER**

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

#### **COPYRIGHTS**

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 25 Apr, 2022 Page 2 of 2