

## Carboset® 552 Acrylic Dispersion

Low molecular weight, Soft thermoplastic blend

Carboset® 552 is a soft thermoplastic polymer offering a hardness and molecular weight intermediate of two established polymers, Carboset® 515 and Carboset® 514H. This innovation takes advantage of the tackiness of Carboset 515 and the cohesive strength of Carboset 514H to offer an improved polymer to the adhesive industry. The lower molecular weight of Carboset 552, in comparison to that of Carboset 514H, offers easier alkali resolubility for applications where removability is desired. In addition to adhesive applications, Carboset 552 is recommended as a pigment dispersant and as a polymeric plasticizer for other hard polymeric coatings. The lower molecular weight of Carboset 552 makes it particularly useful as an additive in other systems to promote adhesion, flow, leveling and pigment dispersion. The viscosity of Carboset 552 can be reduced by the addition of water and increased by the addition of a neutralizing agent such as ammonium hydroxide. Carboset 552 is compatible with a variety of organic solvents, including lower alcohols, ketones and esters. Typical applications: Adhesives | Polymeric plasticizer for hard polymeric coatings | Pigment dispersion

### FEATURES AND BENEFITS

- Adhesion
- Alkali Strippable
- Crosslinkable
- Hardness

### CHARACTERISTICS

Characteristic Name	Value
% Weight Solids	36.0 – 38.0
Acid Number (mg KOH/g)	60.0 – 70.0
Appearance	Translucent Liquid
Brookfield Viscosity (cps)	200 – 800
Tg (°C)	3
pH Value	6.7 – 7.5

### APPLICATIONS

- Building & Construction Coatings
- Particle Dispersions

### AVAILABLE REGIONS

- North America

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.