PERFORMANCE COATINGS

PRODUCT DATA SHEET

Lanco™ Flow UA 50

Acrylic Flow Modifiers

Lanco™ Flow UA50 is a flow and leveling agent that eliminates surface defects such as craters, pinholes and orange peel. Based on acrylic chemistry, Lanco Flow UA50 is compatible in a wide range of coatings including thermosetting alkyds, acrylics, polyesters and epoxies; air-dry alkyds, acrylics and nitrocellulose lacquers; and 2K epoxies and urethanes. Lanco Flow UA50 is particularly recommended for coil coatings. Due to low viscosity, Lanco Flow UA50 can be added at any manufacturing stage including post addition to enhance the wetting properties.

FEATURES AND BENEFITS

- Flow & Leveling
- · Re-Coatability

Solvent Based

CHARACTERISTICS

Characteristic Name	Value
Addition Levels (% on total formula)	The recommended addition level of Lanco Flow UA50 is 0.20-2%, based on total formulation weight.
Appearance	Pale Yellow Liquid
Chemical Type	Acrylic Polymer
Density (g/cm3 @ 20°C)	0.93
Incorporation Recommendations	Lanco Flow UA50 can be added under mechanical stirring at any point of the manufacturing process.
Solvent	Aromatic 100
Storage & Handling	Store in original, unopened containers.
Viscosity (cps)	250

APPLICATIONS

• Industrial OEM Coatings

Protective Coatings

Published on 26 May, 2023

Lanco™ Flow UA 50 Performance Coatings

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAlCustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

Published on 26 May, 2023 Page 2 of 3

Lanco™ Flow UA 50 Performance Coatings

COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 26 May, 2023 Page 3 of 3