

**Solsperse™ AC5120**

A partially neutralized polyacrylate dispersant for ceramic water slurries

Solsperse™ AC5120 is a partially neutralized 63% solids active polyacrylic acid dispersant in water which offers significant technical advantages in a range of ceramic processing methods, including slip casting, gel casting, spray drying, isostatic pressing, and uniaxial pressing. Solsperse™ AC5120 should be dissolved in the water and binder mixture before the addition of ceramic solids. Addition levels should be based on the surface area of the ceramic / filler. The dosage level is typically 2mg active dispersant per square meter of ceramic filler surface area. This is simply the surface area divided by 5. Small particle size / higher surface area may result in a higher dispersant demand.

**FEATURES AND BENEFITS**

- Dispersant Efficiency
- High Pigment Loading
- High Solids Dispersant
- Ideal for Ceramic Formulations
- Low Foaming
- Low Viscosity
- Stability
- Water Based

**CHARACTERISTICS**

Characteristic Name	Value
Appearance	Colorless to amber, clear to slightly hazy liquid
Density (lb/gal @ 25°C)	1.2
Solids (wt %)	63
Viscosity (cps @ 25°C)	950
pH Value (as supplied)	2.6

**AVAILABLE REGIONS**

- Asia Pacific
- EMEAI
- Latin America
- North America

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. **TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION.** Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. **BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY.** You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

## COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.