

Solsperse™ AC5120

A partially neutralized polyacrylate dispersant for ceramic water slurries

Solsperse™ AC5120 is a partially neutralized 63% solids active polyacrylic acid dispersant in water which offers significant technical advantages in a range of ceramic processing methods, including slip casting, gel casting, spray drying, isostatic pressing, and uniaxial pressing. Solsperse™ AC5120 should be dissolved in the water and binder mixture before the addition of ceramic solids. Addition levels should be based on the surface area of the ceramic / filler. The dosage level is typically 2mg active dispersant per square meter of ceramic filler surface area. This is simply the surface area divided by 5. Small particle size / higher surface area may result in a higher dispersant demand.

FEATURES AND BENEFITS

- Dispersant Efficiency
- High Pigment Loading
- High Solids Dispersant
- Ideal for Ceramic Formulations
- Low Foaming
- Low Viscosity
- Stability
- Water Based

CHARACTERISTICS

Characteristic Name	Value
Appearance	Colorless to amber, clear to slightly hazy liquid
Density (lb/gal @ 25°C)	1.2
Solids (wt %)	63
Viscosity (cps @ 25°C)	950
pH Value (as supplied)	2.6

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. **THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.** Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. **BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.**

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.