

### **PERFORMANCE COATINGS**

### PRODUCT DATA SHEET

#### **Humectant GRB5**

A low VOC Humectant.

Humectant GRB5 is a 100% active humectant designed to improve the tip drying, open time and re-dispersibility of agglomerates in aqueous pigment pastes, coatings and inks. It offers a lower VOC and sVOC alternative to glycols traditionally used as humectants. It can improve freeze/thaw stability, as well as color strength and compatibility of dispersions. Humectant GRB5 is suitable for use in eco-label paints and colorants.

#### **FEATURES AND BENEFITS**

Humectant

Open Time

## **CHARACTERISTICS**

Characteristic Name	Value
Appearance	Pale to straw coloured liquid
Density (g/ml)	Approx. 1.14
Incorporation Recommendations	A maximum dosage of 5% in the final coating is recommended so as not to affect the water resistance of the coating. Dosages for colorant and pigment dispersion applications should be adjusted with this recommendation in mind.
pH Value	Approx. 7
Solids (wt %)	100
Storage & Handling	During prolonged low temperature storage or transportation, some crystallization or turbidity may occur. The should not affect the product performance, and gentle warming to 25-35°C with agitation should cause it to become homogenous again.

## **REGULATORY**

APEO-Free¹

Ultra Low VOC⁵

<sup>5</sup>Suitable for coating formulations where less than 50 g/l VOC (US EPA Method 24) or 25 g/l VOC (ISO 11890-1, Method 2) is desired based on calculations.

## **APPLICATIONS**

• Building & Construction Coatings

• Transportation Coatings

Published on 24 Jun, 2024 Page 1 of 3

<sup>&</sup>lt;sup>1</sup>Not intentionally added to the composition of this product

Humectant GRB5 Performance Coatings

## **AVAILABLE REGIONS**

- Asia Pacific
- EMEAI
- Latin America
- North America

### RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

#### **REGULATORY STATUS**

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

### **DISCLAIMER**

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

Published on 24 Jun, 2024 Page 2 of 3

Humectant GRB5 Performance Coatings

# COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 24 Jun, 2024 Page 3 of 3