

**Solsperse™ W320 Aqueous Dispersant**

A 40% active APE-free polymeric dispersant in water

Solsperse™ W320 is a 40% active polymeric hyperdispersant designed for rapid wetting, dispersion and stabilization of transparent iron oxide used in automotive coatings and wood finishes. Solsperse W320 is also expected to be effective across a wide range of inorganic pigments, including TiO<sub>2</sub>. It provides outstanding transparency, high pigment loadings and excellent stability, especially when used in binder-free dispersions. Coatings formulated with Solsperse W320 deliver very high-performance properties in both 2K and 1k water-based finishes.

**FEATURES AND BENEFITS**

- Color Development
- Dispersant Efficiency
- Fast Wetting
- High Color Strength
- High Pigment Loading
- High Transparency
- Improved Coloristic
- Low Viscosity
- Milling Efficiency
- Particle Size Reduction
- Water Based

**CHARACTERISTICS**

Characteristic Name	Value
Appearance	Pale yellow to amber liquid
Density (g/ml)	1.05
Freezing Point (°C)	0
Gardner Colour	max 9
Solvent Boiling Point (°C)	100
pH Value (10% in Water)	Approx. 3

**REGULATORY**

- Nestle Guidance | Note: Packaging Inks
- Swiss Ordinance (Annex 10 to the Ordinance)

## APPLICATIONS

- Building & Construction Coatings
- Industrial OEM Coatings
- Protective Coatings
- Analog Printing Inks
- Particle Dispersions
- Transportation Coatings

## AVAILABLE REGIONS

- Asia Pacific
- EMEA

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.

