

Hycar® 2679D Acrylic Emulsion

Acrylic Emulsion

Hycar® 2679D emulsion is a heat-reactive acrylic latex polymer. It provides outstanding wash and dry cleaning resistance and is not easily soiled. It achieves discoloration resistance to light and heat aging -- the later being outstanding even in its own class of acrylic latexes. But most important is that these outstanding properties are achieved with a minimum heat requirement. This, combined with the latex's ease of compounding because of its good colloidal stability, can affect significant cost savings. Hycar 2679 emulsion is suggested for use as a saturant and/or backcoating for textile fabrics, nonwoven fabrics and paper. Its pigment binding properties should make it well suited for use in print pastes, textile printing inks and pigmented coatings such as leather finish formulations. Its adhesive characteristics are such that it has been used as a base for formulating excellent laminating adhesives, packaging adhesives and flocking adhesives.

FEATURES AND BENEFITS

- Abrasion Resistance
- Adhesion
- Block Resistance
- Chemical Resistance
- Crock Resistance
- Crosslinkable
- Durable
- Flexible
- Fold Resistance
- Heat Reactive
- Mechanical Stability
- Solvent Resistance
- Water Resistance

CHARACTERISTICS

Characteristic Name	Value
% Weight Solids	48.0-50.5
Brookfield Viscosity (cps)	100 - 180
Specific Gravity: Latex	1.063
Specific Gravity: Solids	1.135
Surface Tension (Dynes/cm)	45
Tg (°C)	-3
pH Value	3.1-5.4

REGULATORY

- APEO-Free¹
- FDA

¹Not intentionally added to the composition of this product

APPLICATIONS

- Fiberglass Media
- Filtration Media
- General Paper & Nonwovens
- Home Furnishing Coatings
- Technical Textile Coatings

AVAILABLE REGIONS

- Asia Pacific
- EMEA
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND

FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.

