

**PrintRite™ DP 339 Ink Receptive Coating**

Formulated Coating for Inkjet Printing on Films

PrintRite™ DP 339 is an economical, matte digital ink receptive topcoat for polyester, polyolefin and vinyl films. It is specifically designed for water-based pigment inkjet printing. PrintRite™ DP 339 provides improved color gamut, ink density, print contrast and resolution with instant ink drying. The product is also able to withstand prolonged water soak tests, wet rub tests and when printed with water-based pigment inkjet inks is capable of passing BS5609, a testing requirement for self-adhesive drum labels needing International Maritime Dangerous Goods (IMDG) Certification.

**FEATURES AND BENEFITS**

- High Print Quality
- Ideal for inkjet print applications
- Ink Receptive
- Matte
- Printability
- Ready to Use
- Rub Resistance
- Vibrant colors
- Water Resistance

**CHARACTERISTICS**

Characteristic Name	Value
Appearance	White Opaque Liquid
Brookfield Viscosity (cps)	400 - 800 (RV#2 @ 20 rpm)
Solids (wt %)	34.0 - 37.0
pH	9.8 - 10.2

**REGULATORY**

- APEO-Free<sup>1</sup>
- Formaldehyde-Free<sup>1</sup>
- NMP-Free<sup>1</sup>

<sup>1</sup>Not intentionally added to the composition of this product

**APPLICATIONS**

- Digital Printing Coatings

## AVAILABLE REGIONS

- Asia Pacific
- EMEA
- Latin America
- North America

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 90 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. **THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.** Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. **BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.**

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.