

**PrintRite™ DP 358E Ink Receptive Coating**

Ink Receptive Coating for Digital Printing of Textile Materials

Printrite™ DP358E is a custom formulated waterborne ink receptive coating designed for the knife coating of textile substrates for UV and Latex inkjet printing media. Printrite™ DP358E is suitable for use with polyester textile media and is particularly focused on display backlit graphic type applications. Printrite™ DP358E can be used in combination with a primer coating such as Printrite™ DP120E in order to achieve maximum hold-out of the ink receptive coating. Printrite™ DP358E has been designed to provide high quality digital print images, with a glossy finish, excellent rub, scratch and fold resistance on a variety of different synthetic substrates.

**FEATURES AND BENEFITS**

- Flexible
- Glossy
- High Print Quality
- Ideal for fabric applications including synthetics
- Ink Receptive
- Rub Resistance
- Scratch Resistance

**CHARACTERISTICS**

Characteristic Name	Value
Appearance	White Paste
Brookfield Viscosity (cps)	11,000 - 14,000 (#5 Spindle @ 20RPM)
Solids (wt %)	58.5 - 61.5
pH	8.0 - 10.0

**APPLICATIONS**

- Digital Printing Coatings

**AVAILABLE REGIONS**

- Asia Pacific
- EMEA

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.