

# LUBRIZOL<sup>®</sup> 219

Corrosion Inhibitor

## PRODUCT DESCRIPTION

LUBRIZOL 219 is a solvent borne organic phosphate - zinc complex thin-film corrosion inhibitor that can be used as an additive in direct to metal coatings and treatments.

## FEATURES/BENEFITS

- Provides corrosion inhibition for direct to metal coatings
- Effective in combination with corrosion inhibitive pigments

## PHYSICAL CHARACTERISTICS\*

Appearance	Amber solution
Active content (by weight)	75%
Solvent	Aromatic 100
Density @ 15.6°C (60°F)	1.03
Flash point °C (°F)	49 (122)

\* Property values represent typical results only and are not to be considered specifications.

## TYPICAL APPLICATIONS

LUBRIZOL 219 can be used in coatings designed to protect cold-rolled, galvanized, and phosphated steel.

It should be incorporated during the grind stage of manufacturing at addition levels of 0.5 to 3.0%, based on total formula weight

## RECOMMENDED RETEST DATE (RRD) / STORAGE

Lubrizol 219 is available in 200 liter (55-gallon) drums and 20 liter (5-gallon) pails.

RRD: 2 years.

For storage information, please refer to the current Safety Data Sheet.

## REGULATORY STATUS

Please refer to the current Safety Data Sheet (SDS) for regulatory information.

This can be requested at [www.lubrizolcoatings.com](http://www.lubrizolcoatings.com).

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

Trademarks owned by The Lubrizol Corporation © The Lubrizol Corporation 2018, All Rights Reserved. Brecksville, February 2018 LZ219 JNR

The Lubrizol logo consists of the word "Lubrizol" in a bold, sans-serif font, with a blue swoosh underline that starts under the 'L' and ends under the 'l'.

[www.lubrizolcoatings.com](http://www.lubrizolcoatings.com)