

# SOLTHIX™ T23900

## Synthetic Thickener

PERFORMANCE COATINGS

### Product Description

Solthix™ T23900 polymer is a powdered synthetic thickener based on polyacrylic acid. Solthix T23900 is a synthetic thickener used in aqueous systems for a variety of different purposes in printing, coating or other technical applications. It demonstrates efficient thickening performance, easy wetting behavior, and flexibility in formulation for different end-use. This resin is un-neutralized, and requires addition of ammonium hydroxide (or other appropriate neutralizing agents) to achieve maximum thickening efficiency. Neutralized dispersions of the Solthix T23900 show high viscosity and high yield stress, and can be used for suspending pigments or other particles in an aqueous system.

### Features/Benefits

- Excellent thickening efficiency
- Easy to disperse
- Good suspension properties
- Shear-Thinning

### Physical Characteristics\*

Appearance (wet)	White Powder
Odor	Slightly acetic
Moisture content, %	3.0 max
Viscosity, cP, 25°C	60,000
0.5 wt% mucilage, spindle #6	
Wetting time, 0.5 wt.% dispersion	4 min

\*Property values represent typical results only and are not to be considered specifications

### Typical Applications

Optimum thickening properties at pH 6-9

Textiles

Paints and Coatings

Printing and Packaging

## Shelf Life/Storage

For shelf life information please refer to the packaging label and the Certificate of Analysis. It provides the date of manufacturing (DOM) and a recommended re-test date (RRD).

Material should be stored on pallets in closed areas. A storage temperature of 30°C should not be exceeded.

## Regulatory Status

Please see the product's current safety data sheet, SDS, for regulatory information. It can be requested at [www.lubrizolcoatings.com](http://www.lubrizolcoatings.com).

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2018, All Rights Reserved.

