

## **PERFORMANCE COATINGS**

### Solthix<sup>™</sup> T200 Rheology Control Additive

Synthetic thickener

Solthix<sup>™</sup> T200 is a thickener used in aqueous textile printing systems to obtain high quality prints. It demonstrates ion insensitivity to electrolytes which may be present in dye printing systems, combined with efficient thickening performance.

# FEATURES AND BENEFITS

• Shear-Thinning

• Thickener

## **CHARACTERISTICS**

Characteristic Name	Value
Appearance	White powder
Moisture Content (%)	3
Odor	Slightly acetic
Viscosity (1.0% solution @ pH 7)	16,000 mPas (Brookfield RVT)
Viscosity (1.0% solution in 1.0% NaCl)	11,000 mPas

## APPLICATIONS

- Analog Printing Inks
- Apparel Coatings
- Custom Textile Formulations

- Home Furnishing Coatings
- Technical Textile Coatings
- Transportation Textile Coatings

# **AVAILABLE REGIONS**

- Asia Pacific
- EMEAI

### **RECOMMENDED STORAGE AND RE-TEST DATE**

Lubrizol recommends retesting quality after 730 days. See SDS for storage conditions and handling instructions.

#### **REGULATORY STATUS**

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

#### DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.