PERFORMANCE COATINGS

PRODUCT DATA SHEET

Aptalon™ W8060

Water-borne, self-crosslinking polyurethane dispersion using patented Aptalon™ polyamide technology

High-performance wood flooring applications allowing for globally compliant formulations. Coating formulations made with Aptalon technology are designed to deliver very high performance properties in a 1K system and provide hydrolysis resistance, hardness and chemical resistance that outperforms other waterborne polyurethane chemistries and matches or exceeds many 2K waterborne finishes without the need for external cross-linkers.

FEATURES AND BENEFITS

- · Abrasion Resistance
- · Chemical Resistance
- · Contains Bio-Based Content
- Durable

- Hardness
- Scratch Resistance
- · Self-Crosslinking
- Toughness

CHARACTERISTICS

Characteristic Name	Value
% Volume Solids	33.0
% Weight Solids	36.0
Appearance	Milky White Dispersion
Brookfield Viscosity (cps)	< 500
Density (g/cc @ 25 °C)	1.05
Density (lb/gal @ 25 °C)	8.78
Freeze/Thaw Stability	Protect from Freezing
MFFT (°C)	59
pH Value	7.5 - 8.5
Volatile Organic Compounds (wt. %)	0.85 TEA

REGULATORY

• APEO-Free¹ • NMP-Free¹

¹Not intentionally added to the composition of this product

Published on 23 Jan, 2024 Page 1 of 3

Aptalon™ W8060 Performance Coatings

APPLICATIONS

- · Building & Construction Coatings
- Industrial OEM Coatings

- · Technical Textile Coatings
- Transportation Textile Coatings

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY, OR TIMELINESS OF ANY INFORMATION. Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY. You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as

Published on 23 Jan, 2024 Page 2 of 3

Aptalon™ W8060 Performance Coatings

permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.

Published on 23 Jan, 2024 Page 3 of 3