

PERFORMANCE COATINGS

Carboset® RPT 3030 Acrylic Emulsion

High solids, 100% acrylic, an elastomeric polymer that is ASTM D6083 compliant

Carboset® RPT 3030 is a high solids, water-based, 100% acrylic emulsion specifically developed as an elastomeric polymer for primers and topcoats. It is ASTM D6083 compliant for roof coatings. Carboset RPT 3030 can be applied over aged concrete, asphaltic felts, BUR, modified bitumen, and single plies, including EPDM. It can be used as a topcoat, primer or self-priming system, allowing customers to leverage a single polymer for multiple construction applications. Carboset RPT 3030 has superior tensile strength in combination with high elongation capability. This makes it a superior product for EPDM roofing, as high elongation capability enables it to withstand the mechanical stresses imposed by the substrate while its low Tg allows for a broad range of application climates. Less than 50 g/l (US) and less than 10 g/L (EU) VOC capable.

FEATURES AND BENEFITS

- Adhesion
- Dirt Pick-Up Resistance
- Durable
- Elastomeric
- Flexible

- High Solids
- Mechanical Stability
- Tear Resistance
- UV Resistance
- Water Resistance

CHARACTERISTICS

Characteristic Name	Value
% Volume Solids	53.0
% Weight Solids	55.0
Appearance	Milky White
Density (lb/gal @ 25 °C)	8.81
Freeze/Thaw Stability	Protect from freezing
Specific Gravity	1.06
Tg (°C)	-35
pH Value	8.0

REGULATORY

APEO-Free¹

Low VOC⁴

¹Not intentionally added to the composition of this product

⁴Suitable for coating formulations where less than 140 g/l VOC (US EPA Method 24) or 75 g/l VOC (ISO 11890-1, Method 2) is desired based on calculations.

APPLICATIONS

• Building & Construction Coatings

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES,

EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.