

PERFORMANCE COATINGS

PowderAdd™ 9081 Powder Coating Additive

Structuring Additive for Powder Coating

PowderAdd™ 9081 is a silicone-free modified synthetic wax used to provide a coarse structure in powder coatings. It can be applied to produce coarse structures, hammertone and antique finishes.

FEATURES AND BENEFITS

- · Consistent structure development
- · Excellent control of coarse structuring effects
- Ideal for Powder Coatings Formulations
- Robust structure patterns regarding durable extrusion

CHARACTERISTICS

| Characteristic Name | Value |
|--------------------------------------|---|
| Addition Levels (% on total formula) | 0.8-1.2% |
| Appearance | Whitish Powder |
| Chemical Type | Modified Synthetic Wax |
| Density (g/cm3 @ 25°C) | 1.4 |
| Incorporation Recommendations | PowderAdd 9081 must be incorporated into the powder premix prior to extrusion. To achieve a coarse structure, acrylic flow modifiers must be left out of the formulation. |
| Particle Size Dv50 (µm) | ≤140 |

APPLICATIONS

• Industrial OEM Coatings

AVAILABLE REGIONS

- Asia Pacific
- EMEAI
- Latin America
- North America

REGULATORY STATUS

Published on 15 Sep, 2021 Page 1 of 2

PowderAdd™ 9081 Performance Coatings

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at www.lubrizol.com/coatings.

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAlCustomerAssistance@Lubrizol.com | Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

DISCLOSURE

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, Inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Product safety information required for safe use is not included. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE FROM YOUR LUBRIZOL REPRESENTATIVE, OR DISTRIBUTOR.

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2020, All Rights Reserved.

Published on 15 Sep, 2021 Page 2 of 2