

**CARBOSET® CA-600L**

Low VOC, Low Odor, 100% Acrylic, Self-Crosslinking

Carboset® CA-600L is a water-based, low odor, 100% acrylic, self cross-linking, polymer emulsion specifically developed for horizontal masonry clear, stain and opaque coatings. High performance coatings can be formulated at <100 g/L VOC to protect and enhance the appearance of a variety of concrete based construction materials for residential and commercial applications. Carboset CA-600L provides a unique combination of properties for a wide range of horizontal masonry coatings. Carboset CA-600L based coatings do not blush, have great exterior durability, and adhere well leading to long lasting, attractive coatings. They also provide good chemical resistance enhancing appearance by resisting discoloration from dirt and spills. Carboset CA-600L based coatings do not yellow and can enhance the color of the substrate when applied in two coats. Good early water resistance and fast dry time provide for faster application and fewer concerns for rain after application. Contractors have reported that Carboset CA-600L based coatings are easier to apply when used side by side with existing commercial coatings. Carboset CA-600L can be used in clears, stains and fully pigmented systems directly on cementitious substrates, in cementitious coatings, over acid stains and over substrates previously treated with latex coatings leading to greater formulation flexibility.

**FEATURES AND BENEFITS**

- Abrasion Resistance
- Adhesion
- Alkali Resistance
- Block Resistance
- Chemical Resistance
- Dirt Pick-Up Resistance
- Fast Drying
- Film Clarity
- Glossy
- Hot Tire Pick-Up Resistance
- Hydrophobic
- Non-Yellowing
- Self-Crosslinking
- Solvent Resistance
- Stain Resistance
- UV Resistance
- Water Resistance
- Weatherability

**CHARACTERISTICS**

Characteristic Name	Value
% Weight Solids	41.0 - 43.0
Appearance	Milky white
Brookfield Viscosity (cps)	15 - 200
Density (g/cc @ 25 °C)	1.05
Freeze/Thaw Stability	Yes (Requires up to 24 hours to thaw)
MFFT (°C)	35

Characteristic Name	Value
pH Value	7.9 - 8.6
Tg (°C)	55

## REGULATORY

- APEO-Free<sup>1</sup>
- Low VOC<sup>4</sup>

<sup>1</sup>Not intentionally added to the composition of this product

<sup>4</sup>Suitable for coating formulations where less than 140 g/l VOC (US EPA Method 24) or 75 g/l VOC (ISO 11890-1, Method 2) is desired based on calculations.

## APPLICATIONS

- Building & Construction Coatings

## AVAILABLE REGIONS

- Asia Pacific

## RECOMMENDED STORAGE AND RE-TEST DATE

Lubrizol recommends retesting quality after 365 days. See SDS for storage conditions and handling instructions.

## REGULATORY STATUS

Please see the product's current material safety data sheet, SDS, for regulatory information. You can request an SDS at [www.lubrizol.com/coatings](http://www.lubrizol.com/coatings).

Should you have questions on additional topics, please feel free to contact your Lubrizol representative or one of our regional Customer Assistance groups listed here:

America: AmerLZAMCustomerAssistance@Lubrizol.com | Europe: EMEAICustomerAssistance@Lubrizol.com |

Asia: APCustomerAssistance@Lubrizol.com | Brazil: BrazilQualityLZAM@Lubrizol.com

## DISCLAIMER

Lubrizol Advanced Materials, Inc. ("Lubrizol") hopes that you have found the information provided helpful, but you are cautioned that this material, including any prototype formulas, is for informational purposes only and you are solely responsible for making your own assessment of appropriate use of the information. **TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, LUBRIZOL MAKES NO REPRESENTATIONS, GUARANTEES, OR WARRANTIES (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR REGARDING THE COMPLETENESS, ACCURACY,**

**OR TIMELINESS OF ANY INFORMATION.** Lubrizol does not guarantee how the materials referenced herein will perform in combination with other substances, in any methods, conditions, or processes, with any equipment, or in non-laboratory environments. **BEFORE COMMERCIALIZATION OF ANY PRODUCT CONTAINING THESE MATERIALS, YOU SHOULD THOROUGHLY TEST SUCH PRODUCT, INCLUDING HOW THE PRODUCT IS PACKAGED, TO DETERMINE ITS PERFORMANCE, EFFICACY, AND SAFETY.** You are solely responsible for the performance, efficacy, and safety of any products you manufacture. Lubrizol shall not be liable, and you shall assume all risk and responsibility for, any use or handling of any material. Any claims may not be approved in all jurisdictions. Any entity making claims related to these products is responsible for complying with local laws and regulations. Nothing contained herein is to be considered as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner, and it is your sole responsibility to determine if any issues related to patent infringement of any component or combination of components relating to the information provided exists. You acknowledge and agree that you are using the information provided herein at your own risk. If you are dissatisfied with the information provided by Lubrizol, your exclusive remedy shall be to not use the information.

## COPYRIGHTS

Trademarks owned by The Lubrizol Corporation or its affiliates. © The Lubrizol Corporation 2022, All Rights Reserved.